

HIGH OUTPUT

**TWO SIZES,
UP TO 240 CUBIC FOOT CAPACITY**

SPREAD ALMOST ANYTHING

SAVE TIME & MONEY!



FARMERS TALK, WE LISTEN

We design our spreaders by listening carefully to what farmers say, then deliver extra value by using the highest quality materials with a firm commitment to uncompromising workmanship.

Our motto of "Farmers talk, we listen" isn't just a clever soundbite. It's why, based on farmers' feedback, we designed smaller high output spreaders that run the same material and produce the same quality spread pattern as our larger units, but can be operated with a 100 HP or smaller tractor or with horses and power cart.

Industry-Best Spread Pattern!

Our spread pattern is the best in the industry. Lanco's high output spreader design makes large clumps literally impossible - there's simply not enough space for material to come out without being broken up by the beaters and spinners. This allows topdressing and no-tilling without hotspots and dead zones.

ONE MACHINE DOES IT ALL!

- Lime
- Litter
- Biosolids
- Penpack (Bedding Pack)
- Horse Manure
- & more!

SPREAD WITHOUT CHANGING ATTACHMENTS

MADE IN LANCASTER COUNTY TO WORLD-CLASS STANDARDS

BETTER SPREADING MADE SIMPLE

717-556-4143

WWW.LANCOEQUIPMENT.COM

LANCO SPREADERS

MORE HIGH QUALITY FEATURES COME STANDARD



Specifications	Model LS-1800	Model LS-2400
Hopper Height	41 inches	41 inches
Hopper Width	76.5 inches	76.5 inches
Hopper Length	12 ft.	16 ft.
Hopper Capacity, Struck Level	180 Cubic Feet, 145 Bushels, 7 Cubic Yards	240 Cubic Feet, 193 Bushels, 9 Cubic Yards
Overall Height	8'9"	8'9"
Overall Width	76.5 inches	76.5 inches
Overall Length	22'	26'
Suspension	Single Axle	Single Axle
Capacity	6 tons	8 tons
Recommended Minimum Horsepower	65	85
Loading Height	84"	84"

Standard Features	Options
Mechanical PTO Driven Spinners and Beaters (1,000RPM), Tractor Hydraulic Web*	Walking Beam
4.25x65R22.5 Truck Tires	Work Lights
Transport Lights	2 Camera System for Monitoring Material and Spread Pattern
Hydraulic Endgate	Flotation Tires
304 Stainless Beater Teeth	Disk Brakes
	Extension Sides
	Second Gearbox**
	Engine Driven Hydraulics For Web



*Tractor Hydraulics Require 16 GPM To Operate.

**Second Gearbox Requires 30 GPM To Operate.

BETTER SPREADING MADE SIMPLE

717-556-4143

WWW.LANCOEQUIPMENT.COM

LANCO
SPREADERS