

# HIGH OUTPUT, HEAVY DUTY

**TWO SIZES,  
UP TO 385 CUBIC FOOT CAPACITY**

# SPREAD ALMOST ANYTHING

**SAVE TIME, MONEY & FUEL!**

**Incredible 70-90 ft. spread widths**  
(depending on material)



## FARMERS TALK, WE LISTEN



Twin webs allow for material to be fed out the 62" wide opening and into the same 18" horizontal beaters as the larger machines use. From there the spinners spread your material evenly across the pattern. Bridging is impossible...

**W**e design our spreaders by listening carefully to what farmers say, then deliver extra value by using the highest quality materials with a firm commitment to uncompromising workmanship.

Our motto of "Farmers talk, we listen" isn't just a clever soundbite. It's why, based on farmers' feedback, we designed smaller high output spreaders that run the same material and produce the same quality spread pattern as our larger units, but can be operated with a smaller tractor and loader.

### Industry-Best Spread Pattern!

Our spread pattern is the best in the industry. Lanco's high output spreader design makes large clumps literally impossible - there's simply not enough space for material to come out without being broken up by the beaters and spinners. This allows topdressing and no-tilling without hotspots and dead zones.

### ONE MACHINE DOES IT ALL!

- Lime
- Litter
- Biosolids
- Penpack (Bedding Pack)
- Horse Manure
- & more!

**SPREAD WITHOUT CHANGING ATTACHMENTS**

**MADE IN LANCASTER COUNTY TO WORLD-CLASS STANDARDS**

**BETTER SPREADING MADE SIMPLE**

717-556-4143

[WWW.LANCOEQUIPMENT.COM](http://WWW.LANCOEQUIPMENT.COM)

**LANCO**  
SPREADERS

# MORE HIGH QUALITY FEATURES COME STANDARD



Specifications	Model LS-3150	Model LS-3850
Hopper Height	45.25 inches	45.25 inches
Hopper Width	92.5 inches	92.5 inches
Hopper Length	18 ft.	22 ft.
Hopper Capacity, Struck Level	315 Cubic Feet, 253 Bushels, 11.5 Cubic Yards	385 Cubic Feet, 309 Bushels, 14.25 Cubic Yards
Overall Height*	10'6"	10'6"
Overall Width*	92.5 inches	92.5 inches
Overall Length	29'	33'
Suspension	Walking Beam	Walking Beam
Capacity	13 tons	17 tons
Recommended Minimum Horsepower**	150	170

*\*When Using Standard 4.25x65R22.5 Truck Tires \*\*Depending Upon Desired Tons/Acre, Material Composition and Travel Speed, Larger Tractors May Be Necessary.*

Standard Features	Options
Mechanical PTO Driven Spinners and Beaters (1,000 RPM), Tractor Hydraulic Web*	Single Axle
4.25x65R22.5 Truck Tires	Work Lights
Transport Lights	2 Camera System for Monitoring Material and Spread Pattern
Hydraulic Endgate	Flotation Tires
304 Stainless Beater Teeth	Disk Brakes
	Extension Sides

*\*Tractor Hydraulics Require 30 GPM To Operate.*



**BETTER SPREADING MADE SIMPLE**

717-556-4143  
WWW.LANCOEQUIPMENT.COM

**LANCO**  
SPREADERS